


CDM-/TP Medium Wattage Elite

Protected, high efficiency, discharge lamps with stable colour over lifetime and a crisp, sparkling light. Features double UV block quartz sleeves and a hard glass outer bulb for use in open fixtures, with reduced fading risks. Requires ballast and igniters, and a high current protection device for CDM-TP is mandatory (IEC 1167).

Electronic gear can be used to increase lamp-life, improve system efficacy, and offer flicker-free operation.



Product ID	Overall Length	Diameter	Light Centre Length	Arc Length
	C max.	D max.	L nom.	O nom.
210W	188	29	92	12.1
315W	188	29	92	14

Dimensions in mm

CDMT/TP MW ELITE

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
CDMTPMWEL210W93	MASTERCLOUR CDM-TP MW Elite 210W/930 PGZX18 (P)	210	PGZX18	23100	27000	3000	12	12
CDMTPMWEL210W94	MASTERCLOUR CDM-TP MW Elite 210W/942 PGZX18 (P)	210	PGZX18	22100	30000	4200	12	12
CDMTPMWEL315W93	MASTERCLOUR CDM-TPMW Elite 315W/930 PGZX18 (P)	315	PGZX18	36200	30000	3000	12	12
CDMTPMWEL315W94	MASTERCLOUR CDM-TPMW Elite 315W/942 PGZX18 (P)	315	PGZX18	34700	30000	4200	12	12