


PL-C 4-PIN

PL-C lamps are compact, single ended fluorescent lamps. All require external control gear which normally comes complete with the luminaire. 4-pin (dimming) option.



Product ID	Base Face to Base Face A max.	Insertion Length B max.	Overall Length C max.	Diameter DI max.
13W	97.5	117	131.9	27.1
18W	109.5	129	143.9	27.1
26W	130.7	150	164.9	27.1


Dimensions in mm

PL-C 4-PIN

Shortcode	Wattage (W)	Cap Base	Luminous Flux Lamp (lm)	Average Lifetime (hrs)	Colour Rendering Index (Ra)	Colour Temp (K)	Min Order Quantity	Carton Qty
PLC13W8304P	13	G24q-1	900	10000	83	3000	10	50
PLC13W8404P	13	G24q-1	900	10000	82	4000	10	50
PLC18W8304P	18	G24q-2	1200	10000	83	3000	10	50
PLC18W8404P	18	G24q-2	1200	10000	82	4000	10	50
PLC26W8274P	26	G24q-3	1800	10000	83	2700	10	50
PLC26W8304P	26	G24q-3	1800	10000	83	3000	10	50
PLC26W8404P	26	G24q-3	1800	10000	82	4000	10	50

MASTER PL-L 4-PIN

PL-L lamps have two parallel fluorescent tubes and a 4-pin base. Dimming possible on electronic gear.



Product ID	Base Face to Base Face A max.	Insertion Length B max.	Overall Length C max.	Diameter D max.	Diameter DI max.
18W	194.2	220	226.0	37.7	18
36W	384.2	410	416.6	37.7	18
40W	509.2	535	541.6	37.7	18
55W	509.2	535	541.6	37.7	18

Dimensions in mm

MASTER PL-L 4-PIN

Shortcode	Wattage (W)	Cap Base	Luminous Flux Lamp (lm)	Average Lifetime (hrs)	Colour Rendering Index (Ra)	Colour Temp (K)	Min Order Quantity	Carton Qty
PLL18W8304P	18	2G11	1200	15000	82	3000	25	25
PLL18W8404P	18	2G11	1200	15000	82	4000	25	25
PLL36W8404P	36	2G11	2900	15000	82	4000	25	25
PLL55W8304P	55	2G11	4800	20000	82	3000	25	25
PLL55W8404P	55	2G11	4800	15000	82	4000	25	25